

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**

THIS PAGE BLANK (USPTO)

2

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



09/822,850


INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B65D 43/02	A1	(11) International Publication Number: WO 96/16875 (43) International Publication Date: 6 June 1996 (06.06.96)
<p>(21) International Application Number: PCT/DK95/00467</p> <p>(22) International Filing Date: 23 November 1995 (23.11.95)</p> <p>(30) Priority Data: 1349/94 25 November 1994 (25.11.94) DK</p> <p>(71)(72) Applicant and Inventor: BOCK, Eric [DK/DK]; Valmuevej 6, 4340 Tølløse (DK).</p>	<p>(81) Designated States: AU, CA, JP, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</p> <p style="text-align: center; font-size: 2em;">AC</p>	

(54) Title: DROP-SAFE PLASTICS LID FOR CONTAINER

(57) Abstract

A plastics lid that cannot transfer twisting moment to the lid rim. This has been achieved by means of a deformable zone between the center and the rim of the lid, as well as a flexible connection between the lid membrane and the rim along the lid top. The purpose of the design is, that the lid is better fixed to the container so that it will not fall off when the container is accidentally dropped.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

Drop-Safe Plastics Lid for Container

This invention is concerned with a plastics lid 1 for a container 2, which may be a plastic bucket.

The lid is mainly a snap-on lid.

- 5 It may be designed for a round, quadrangular or oval container with an exterior 3 or interior 4 snap-rim.

Known constructions of pastics lids have the drawback, that they come off the container, if the latter one is being dropped, or they are made so solid that they must be cut from the container, in order to get access to the contents.

The purpose of this invention is that of being able to produce a lid that does not come off the container, if the latter one is being dropped, but which can still be fairly easily taken off the container.

15 When a container is being dropped, a large excess pressure is formed inside the container as it hits the ground. It seems like a blow on the under part of the lid, and this blow causes a torsional moment on the rim of the lid 5 on all existing lid constructions. This torsional moment is the principal reason why the lid is coming off when the container is being dropped.

This is why the rim 5 of the lid in this invention is flexibly connected to the center of the lid 6 along the top 7 of the rim, thus preventing a moment that would twist the lid off the container.

25 Even if the rim of the lid stays on the container, there is a risk that the lid will split when dropped, due to the high pressure inside the container, which will act like a blow on the under part of the lid.

30 In order to minimize this blow on the under part of the lid, this invention comprises a surrounding deformable zone 8 in the lid, between the central zone of the lid 6, and the rim of the lid 5.

This zone allows the drop energy to be absorbed on a prolonged section by the deformation of the lid, and the blow on the lid is thereby reduced.

40 Looking at fig. 2 it is easy to imagine, that the center of the lid will bulge at a large inner high pressure, because the two absorption lines 9 will function as hinges.

The drop energy must be absorbed as evenly as possible, in order to reduce the energy peak. This is obtained by using absorption lines 9, reduced wall thickness 8, and/or deformable ribs 10 in the deformable zone.

45 The rather thin-walled ribs 10 will, if they are being used at all, become stretched, thereby contributing to the absorption of the drop energy.

They may be placed either radially or slantwise, and they may be made flat or curved.

5 Of-course, the ribs may also be placed on the upper side of the lid, but they will then be more difficult to clean.

Furthermore, the deformable zone must be designed with consideration of the fact, that conical buckets will be stacked without gaskets on the lids of the buckets stacked below.

10

The stacking must be performed as stable as possible. The flexibility of the deformable zone is, therefore, minimized in the radial direction, whereby the buckets standing on top will cause tensions in the lids.

15 When stacking cylindrical buckets, where the stacking is direct on the rim of the lid, this phenomenon has no importance, and the flexible zone can be designed as a bellows with one, as shown in fig. 4, or more waves.

20 The idea of designing a flexible lid is not new, as will be seen from EPO Patent Application No. 92304118.0, dealing with a lid from sheet metal.

25 But there the flexible zone has been placed inside the area, which is stressed by the buckets stacked on top, and consequently the rim of the lid cannot follow the deformations of the bucket on drop impact, whereby it will more easily fall off.

Furthermore, the drop energy will be transferred as a moment on the rim of the lid, whereby it is twisted off the bucket.

30 In the Danish Patent Application 4949/69 is likewise shown a flexible ditch inside the area, which is stressed by a bucket stacked on the lid. In this case the same drawback as described above appeared in that, when dropped, the deformation of lid and bucket could not take place simultaneously, and consequently the lid was twisted off the bucket.

35

Also the AU Patent Application No. 8138723 dealing with a plastics lid describes a flexible lid. But here only flexibility against a thrust from the side of the container is obtained. The inside high pressure will still twist off the lid from the bucket. Furthermore, a bucket stacked on the lid will be rolling loosely during transportation, and thereby be unstable.

40

45 In EPO Patent Application No. 92250348.7 the central part of the lid is connected somewhere up at the rim-portion, but the aim of the application was not to produce a drop-safe lid, which in fact was not obtained by the shown design of the rim, since, if anything, the lid would roll off the bucket by an internal high pressure inside the bucket.

Fig. 1 shows a vertical cross-section between a lid 1 and the opening of a container 2, where a deformable zone 8 in the lid was obtained by reducing the wall thickness of the sloping surface.

5

The deformable zone 8 is flexibly connected with the rim of the lid 5 in a line 7 along the top of the rim.

10

Fig. 2 shows a vertical cross-section between a lid 1 and the opening of a container 2, where the deformability of the lid was obtained by reducing the wall thickness in two totally or partially surrounding lines 9, which will act as hinges and allow the center 6 of the lid to bulge by an internal high pressure in the container, without transferring a twist moment to the rim of the lid 5.

15

Fig. 3 shows a vertical cross-section between a lid 1, which snaps internally into a container 2 with an internal snap-rim 4. The flexible zone of the lid 8 is connected along a line 7, which can act as hinge with the rim of the lid 5.

20

Fig. 4 shows a vertical cross-section between a lid 1, which snaps internally into a container 2 with an internal snap-rim 4. The flexible zone of the lid, that in this case is designed as a bellows with a reduced wall thickness which thereby allows deformation, is connected along a line 7 with the rim of the lid 5.

CLAIMS

5 1. Plastics lid for container, characterized in that the center part and the rim portion of the lid are flexibly connected through one or more, totally or partly surrounding wall narrowings situated along the top of the lid rim.

10 2. Plastics lid for container in accordance with Claim 1, characterized in that in the ring-shaped zone inside the flexible connection to the lid rim is a deformable area.

15 3. Plastics lid for container in accordance with Claims 1 and 2, characterized in that the deformable area has a thinner wall thickness than the remainder of the lid.

20 4. Plastics lid for container in accordance with Claims 1 and 2, characterized in that the deformable area has one or more totally or partly surrounding absorption lines that can act as hinges.

25

30



35

40



45

50

1/2



2/2



INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 95/00467

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: B65D 43/02

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4449641 A (JORGENSEN ET AL.), 22 May 1984 (22.05.84), column 2, line 31 - line 46, figure 1 --	1-3
X	DE 4222396 A1 (DART INDUSTRIES INC.), 11 March 1993 (11.03.93), column 4, line 16 - line 26, figure 2 --	1,2,4
X	US 3170588 A (J.M. LYON, JR), 23 February 1965 (23.02.65), column 2, line 36 - line 52, figure 5 --	1,2,4
X	WO 9009329 A1 (PANTHER PLAST A/S), 23 August 1990 (23.08.90), figure 2, abstract --	1,2,4

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *B* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

Z document member of the same patent family

Date of the actual completion of the international search

27 March 1996

Date of mailing of the international search report

28-03-1996

Name and mailing address of the ISA/
Swedish Patent Office
Box 5055, S-102 42 STOCKHOLM
Facsimile No. +46 8 666 02 86

Authorized officer

Helena Åkerlund
Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/DK 95/00467

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 4388998 A (UNDERWOOD ET AL.), 21 June 1983 (21.06.83), column 5, line 10 - line 28, figure 6 --	1-3
E	WO 9532128 A1 (AMRAX LTD.), 30 November 1995 (30.11.95), figures 2A, 2B, 3, abstract --	1,2,4
A	US 4378895 A (WOINARSKI), 5 April 1983 (05.04.83), figures 5,5A --	1-4
A	EP 0642983 A1 (BROADWAY COMPANIES, INC.), 15 March 1995 (15.03.95), figure 4 -- -----	1,2,4

INTERNATIONAL SEARCH REPORT

Information on patent family members

05/02/96



International application No.

PCT/DK 95/00467

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A- 4449641	22/05/84	AU-A- 8446182 BE-A, A- 893446 CH-A, B- 656104 DE-A- 3220766 FR-A, B- 2507569 GB-A, B- 2100239 JP-A- 58052052 NL-A- 8202324 SE-A- 8203606	16/12/82 01/10/82 13/06/86 17/02/83 17/12/82 22/12/82 28/03/83 03/01/83 12/12/82
DE-A1- 4222396	11/03/93	AT-A- 136292 AU-B- 634120 BE-A- 1006543 CA-A- 2074858 CH-A- 685695 ES-A- 2065228 FR-A, B- 2681049 GB-A, B- 2259297 GR-A- 92100372 IL-A- 102413 JP-A- 5278753 JP-B- 7100511 LU-A- 88163 NL-A- 9201453 NZ-A- 243571 PT-A- 100833 SE-A- 9202528 US-A- 5147059 ZA-A- 9205439	15/09/95 11/02/93 11/10/94 05/03/93 15/09/95 01/02/95 12/03/93 10/03/93 21/06/93 07/10/94 26/10/93 01/11/95 15/02/93 01/04/93 28/03/95 31/05/94 05/03/93 15/09/92 10/05/93
US-A- 3170588	23/02/65	NONE	
WO-A1- 9009329	23/08/90	AU-A- 5101490 DE-D, T- 69004420 EP-A, B- 0456749 SE-T3- 0456749	05/09/90 19/05/94 21/11/91
US-A- 4388998	21/06/83	NONE	
WO-A1- 9532128	30/11/95	NONE	
US-A- 4378895	05/04/83	AU-B, B- 544003 AU-A- 7850481 CA-A- 1163234 GB-A, B- 2093440 JP-B- 1003750 JP-C- 1529347 JP-A- 57142857	16/05/85 05/08/82 06/03/84 02/09/82 23/01/89 15/11/89 03/09/82
EP-A1- 0642983	15/03/95	NONE	

THIS PAGE BLANK (USPTO)

1/2



2/2

